



**EBSProducts.com**

Ph: 877-955-0515 F:  
714-896-6711

---

## **EC-1 #1000-0070V- Coolant Service Specifications**

- ⇒ A self-contained coolant extraction, flush and change service equipment – reverse flow
- ⇒ Adapter set covers 99% of vehicles
- ⇒ A valve on the adapter allows for regular coolant flow to check thermostat operation and flushing material function, then is opened for reverse coolant service after turning the engine off.
- ⇒ The engine does not have to be at operating temperature to perform the service.
- ⇒ 110 vac powered, fuse protected, converted to 12 vdc operation
- ⇒ 22 ft. power cord with power cord holder attached to cabinet
- ⇒ Easy to use, 3 electrical switches control the service
- ⇒ A reverse flow through the cooling system provided by a combination of pressure (25 psi) at the engine and vacuum at the radiator
- ⇒ **Level Sensor stops fluid flow when ½ G of new fluid remains**
- ⇒ Separate Fill and Vacuum pumps each rated at one gallon per minute
- ⇒ A Prime Valve between service hoses to prime remaining new fluid to the waste tank if desired.
- ⇒ The ends of the adapters are marked to show proper attachment
- ⇒ All quick connects on hoses are double shut off
- ⇒ A controllable handgun wand for vacuuming coolant from the vehicle's radiator and hoses
- ⇒ Equipment cabinet and tanks made from heavy-duty industrial grade polyethylene to provide for the safe and secure containment of 8 gallon new and 8 gallon waste tanks
- ⇒ Cabinet contains a built-in sturdy handle to assist in movement

of the equipment

- ⇒ Locking front wheels and large 8” rear wheels
- ⇒ Easy top fill of new coolant tank
- ⇒ A third 12 vdc, 3.7 gallon per minute rated pump, switched on the rear of the equipment for emptying the waste tank
- ⇒ Additional utility items include, protective gloves, overflow tube clamp, and extension hoses

## **Machine Dimensions**

|                        |                                  |
|------------------------|----------------------------------|
| <b>Height - 44in.</b>  | <b>Depth – 23in.</b>             |
| <b>Width – 24in.</b>   |                                  |
| <b>Weight – 88lbs.</b> | <b>Shipping Weight – 132lbs.</b> |

11-16



