



EBS ATF EQUIPMENT PREP COOLER LINE AND DIPSTICK EXCHANGE

QUICK REFERENCE 7-1-26

EQUIPMENT PREP: FILL NEW TANK thru **FILL PIPE** in Tray. **FILL** as needed-max 8 gal. If Waste visible in Front Tank go to **EMPTY TANK** (Next Step) to remove, if not go to **STEP 1-Cooler Line** or **STEP 6-DIPSTICK**



STEP 4 Press **EXCH. START**. Equip. takes out Used and Insert New in 2/10 Qts. increments. Monitor Exchange -NEW Fluid will decline and the Used Fluid rise until completed – **PRESS STOP** if needed. The Equip. will **STOP** when complete. Leave **ENGINE ON**.



EMPTY TANK Plug into a 110vac outlet. Power ON. **MAIN SCREEN** comes ON – see Pic above. Press **EMPTY TANKS** (Button or F3) for **EMPTY NEW/USED** – see Pic Right. Select **NEW** or **USED**. Insure open fitting on end of proper Hose. **If DIPSTICK EXCHANGE Go to STEP 6**



STEP 5 Use **DIPSTICK**-Check Fluid Level. If adjustment needed **PRESS ADD/REMOVE** Button on **COOLER LINE** SCREEN. **ADD/REMOVE** SCREEN – See Pic >. Indicate amount needed for **FILL** or **REMOVE** – follow instructions. **ENGINE Off**, Remove Adapters, RE-Connect Cooler Lines.



STEP 1 COOLER LINE - ENGINE OFF
Disconnect Cooler Line. Attach Adapters and Service Hoses to Cooler Line - Fluid Hoses to Service Hoses– next Pic. **START the Engine**. If no Fluid Pressure on top left gauge – **STOP** Engine and Reverse Hose Connections. **RETRY**.



STEP 6 DIPSTICK SERVICE – ENGINE OFF. **MAIN SCREEN** Press **DIPSTICK MODE** -see Pic. Input Qts. on **EXCHANGE** Amount Window. Connect the Dipstick Service Hose and Service Hoses to the Service Manifold - **Red Fill Service Line** is Connected to **FILL** side of the Manifold. **Engine OFF**




STEP 2 NOTE: With Engine ON and Fluid Pressure visible, (insert chemicals using small bottle at top left of equip. Hold Insert Switch until completed). **PRESS COOLER LINE** BUTTON on the **MAIN SCREEN** - see Pic 1 above.



STEP 7 Insert **DIPSTICK SERVICE HOSE** into **DIPSTICK TUBE**. Press **DRAIN PAN**, Stops when complete. Press **RESUME REFILL**. New Fluid in until amount matched with Qts. removed. When Refill complete, **ENGINE ON** – **PRESS OK** on Computer - See **STEP 4, after Exch START. Then STEP 8**



STEP 3 COOLER LINE SCREEN ON – See Pic. The **NEW** fluid level and the **Waste Tank** Level will show actual Amounts in the Tanks Adjust the Middle Screen to the Amount wanted for Service. If not enough **NEW** or room for **Waste**, equip will give Warning. Correction required before continuing.



STEP 8 Use **DIPSTICK**-check fluid level. If Adj. needed-replace **DIPSTICK** Service Tube. **PRESS ADD/REMOVE** See Pic>. Indicate amount (Add or Remove) needed to **Correct Level** - Follow Prompts. When complete – go to **Main** Screen. **ENGINE OFF**.

