



## EDS-1 #1000-0075 Dip Stick Fluid Exchange Specifications

- Heavy duty HDPE cabinet with a built in handle, locking front swivel wheels and large 8" rear wheels.
- 110vac fused power converted to 12vdc operation and 12vdc battery power Option available.
- Heavy Duty 110vac 22 ft. power cord with holder.
- 12ft. Heavy Duty 12vdc battery cable attached to cabinet.
- Easy to use electric switch control panel with one VAC Switch and one FILL switch for Tank 1 and one for Tank 2.
- Two – 2 gallon new fluid tanks, front visible, level marked and top filled for your choice of oil, transmission fluids, etc.  
**No brake or coolant fluids.**
- 1.0 GPM rated separate fill pumps, and 6.5 ft. braided service hoses, for each new fluid tank.
- Two- separate 2.5 gallon marked waste tanks – one service tank in top receptacle – one spare in the rear of the cabinet.
- Heavy duty 1/2 GPM vacuum pump – 5.5ft. braided service hose.
- Service manifold to attach the dip stick service hose to both the fill and vacuum service hoses for continuous servicing.
- 4 foot each .180" id and .242" id dip stick service hoses with quick connects.
- Hose drain reservoir for dipstick service hoses.



<u>Machine Dimensions</u>	<b>Machine Weight: 65lbs</b>
Height: 48 1/2in	Shipping Weight: 105lbs
Width: 27in	
Depth: 19in	